


Pin No.	NAME	TYPE	DESCRIPTION
1	DAT 2	I/O/PP	Date Line(bit2)
2	CD/DAT 3	I/O/PP	Card Detect/Date Line(bit3)
3	CMD	PP	Command Response
4	VDD	S	Supply Voltage
5	CLK	I	Clock
6	VSS	S	Supply Voltage Ground
7	DAT0	I/O/PP	Date Line(bit0)
8	DAT1	I/O/PP	Date Line(bit1)



REV.	ECN NO.	MODIFY CONTENT	DATE
A		NEW	2011/10/31

NOTES:
 1) MATERIAL:
 HOUSING:LCP MG350,UL 94V-0,30%/F FILLED;
 COLOR:BLACK
 CONTACT:COPPER ALLOY T=0.15mm
 GROUND:STAINLESS T=0.15mm

2) FINISH:

CONTACT: 1u" GOLD PLATING ON CONTACT AREA
 Tin 100u" MIN PLATING ON SOLDER TAILS
 50u" MIN NICKEL UNDERPLATING OVER ALL
 GROUND: Sn 100u" MIN PLATING ON SOLDER TAILS
 50u" MIN NICKEL UNDERPLATING OVER ALL

3) PRODUCT SPECIFICATIONS:
 VOLTAGE RATING: 50V
 CURRENT RATING: 0.5A
 INSULATION RESISTANCE: 500MEG.OHM MIN
 CONTACT RESISTANCE: 50 MILL.OHM MAX
 OPERATION TEMPERATURE: -20° TO +85°
 DURABILITY: 5000 CYCLES

GENERAL TOLERANCE		DWG NO.	APPR.	WIND	Scale
X±0.45	x.±5'	JYSA0529-005			1:1
X±0.35	.x.±2'	Title	CHKD:		UNIT
.XX±0.25	.xx.±1'	Part NO.	Date		mm
XXX±0.15	.xxx.±0.5'		2011/10/31		
SHEET 1/1					

 杰宇森电子有限公司
 JIE YU SEN ELECTRONIC CO., LTD.