



TD-V系列无油旋片泵

通达产品信息介绍
TOMEDA PRODUCT
INFORMATION INTRODUCTION



TD-4V/TD-8V



TD-10/16/25/40V

可选配过滤器

参数		型号	TD-4V	TD-8V	TD-10V	TD-16V	TD-25V	TD-40V
吸气量 m ³ /h	50Hz		4	8	10	16	25	40
	60Hz		4.8	9.6	12	19.2	30	48
真空度	mbar		150	150	150	150	150	150
功率 KW	50Hz		0.18	0.35	0.37	0.55	0.75	1.25
	60Hz		0.22	0.42	0.44	0.66	0.9	1.5
电压 V	三相	50Hz	360-418	360-418	175-260/300-450	175-260/300-450	190-255/330-440	190-255/330-440
		60Hz	360-480	360-480	202-300/350-520	202-300/350-520	190-290/330-500	190-290/330-500
	单相	50Hz	220-240	220-240	220-240	220-240	220-240	220-240
		60Hz						
电机转速 rpm	50Hz		2800	2800	1420	1420	1420	1420
	60Hz		3360	3360	1700	1700	1700	1700
吸气口径			G1/4	G3/8	G1/2	G1/2	G3/4	G3/4
噪声 db(A)	50Hz		59	58	60	61	62	67
	60Hz		61	61	62	64	67	72
重量kg			7	11.5	15	22	28	39
外形尺寸L*W*H(mm)			184*156*166	261*154*173	426*199*244	454*225*267	502*271*316	570*270*302

☎ 400-151-9885

🌐 www.zjtdpump.com